



Warning Information on Assembly of the Cup Tappets!



The two cup tappets, which look the same from the outside, may only be used in the specific vehicle types allocated to them! They are not interchangeable in any circumstances!

Warning, Important!

Identical geometrical dimensions but not interchangeable because:

- The hydraulic elements have different lowering times (HTE)
- Metering of the quantity of oil
- Different oil specifications
- Surface of the base of the cup is of a different quality (e.g. case-hardened, nitrided, phosphated etc.)
- Type of tappet (labyrinth, run-out-protected or cup tappet with internal deflection)
- Different strengths of spring in the non-return valve
- Different valve strokes for the hydraulic element (HTE) (path in mm)

Possible consequences if this warning is ignored:

- Increased inertial forces (internal)
- Noises in the valve drive
- Higher friction and wear on material
- Material overload
- Greater emission of pollutants and fuel consumption
- Damage to engine!



Example:

Art. no: **420 0043 10**



„Lightweight“ cup tappet (56 gr)

Art. no: **420 0022 10**



„Heavy“ cup tappet (70 gr)

LuK-Aftermarket Service oHG

Paul-Ehrlich-Straße 21
D-63225 Langen
Telefon: +49 (0) 6103-753-0
Telefax: +49 (0) 6103-753-295

info@LuK-AS.de
www.LuK-AS.com

